

SPEC M-AC-003 R1 May, 2003 WATERITE TECHNOLOGIES, INC.

1-885 Keewatin Street Winnipeg, MB Canada R2X 2S7 PHONE: (204) 786-1604 FAX: (204) 783-1599 Email: waterite@waterite.com Website: www.waterite.com

WATERITE TECHNOLOGIES, INC. PRODUCT SPECIFICATION SHEET M-AC-003 R1

COAL BASED, PELLETIZED ACTIVATED CARBON FOR DESULPHURIZATION

A specially formulated, 4mm pelletized carbon for the reduction of hydrogen sulphide and other odour-causing impurities, while retaining all the adsorptive characteristics of conventional activated carbons. A high-performance carbon with a complex pore structure to promote superior adsorption of odorous impurities, trace contaminants and VOCs.

TYPE:	Bituminous coal based, washed, 4mm pellet
SULPHUR:	850 mg/g min.
HARDNESS:	90% min.
ASH:	12% max.
BULK DENSITY:	450 - 510 g/l
MOISTURE:	3% max.
SIZE:	3mm pellet
COLOUR:	Black
PACKAGE:	12.5 kg. (1 cu. ft.) Black paper bags, 42 bags per pallet.
	Pallets are wrapped by plastic wrap to ensure sturdy and
	clean delivery.
TRADE NAME:	CENTURION 7®
MODEL NUMBER:	PJ12X40HS

