

WATERITE TECHNOLOGIES, INC.

3-75 Meridian Drive Winnipeg, MB Canada R2R 2V9 PHONE: (204) 786-1604 FAX: (204) 783-1599 waterite@waterite.com www.waterite.com

## WATERITE TECHNOLOGIES, INC. PRODUCT SPECIFICATION SHEET M-CER-002R3

## STRONG ACID GEL POLYSTYRENE STANDARD WATER SOFTENING CATION EXCHANGE RESIN

TYPE:	Strong acid gel polystyrene, 7% crosslinked
IONIC FORM:	Na
TOTAL CAPACITY:	1.95 meq/ml min.
WATER RETENTION:	45% - 50% max.
BULK DENSITY:	0.78 - 0.85 g/ml
PARTICLE SIZE:	0.315 - 1.25 mm
MAXIMUM TEMP:	120 C
COLOUR:	Amber
PACKAGE:	1 cu. ft white, heavy mil plastic bags, heat sealed at
	ends, plastic lined. 35 bags per pallet. Pallets are
	wrapped by plastic wrap to ensure sturdy and clean delivery.
TRADE NAME:	Excelclear Premium Softening Resin
MODEL NUMBER:	001X7NANS
CERTIFICATION:	WQA Gold Seal, tested and certified by the Water
	Quality Association according to NSF/ANSI 44 for
	materials safety only.



SPEC M-CER-002R3 May, 2005