

# GEMINI

Fusion<sup>2</sup>

NOW EXCLUSIVELY FROM  
WATERITE TECHNOLOGIES



Waterite's new **Gemini Dual Tank Water Softening System** is the latest member of Waterite's Fusion<sup>2</sup> family of advanced water softeners. Perfect for a wide range of light commercial and more-demanding residential applications, the Gemini system employs a single valve that alternates between two mineral tanks, eliminating system downtime for resin bed regeneration and offering users seamless, soft-water service.

**Gemini Dual Tank** softeners range in sizes from 30,000 grains of hardness capacity to 150,000 grains. When one resin tank nears capacity, Gemini's advanced electronic control automatically switches service flow to the second tank and begins the regeneration cycle on the first tank. Practicality, value and ease of operation all combine to make Gemini softeners the obvious choice in a wide range of softening applications.



The heart of the **Gemini Dual Tank** system is its electronic control valve, sharing most critical valve parts with other Fusion<sup>2</sup> products and keeping service simple. Systems boast dual matching tank jackets, bypass valves with connectors and attractive Fusion trim. Gemini packages are rounded out with Waterite's premium resin and comprehensive warranty.

GEMINI WATER SOFTENER SPECIFICATIONS





# GEMINI

Fusion<sup>2</sup>

## GEMINI SERIES TECHNICAL SPECIFICATIONS


Model	Tank (X2)	Valve*	Nominal Peak Flow	CF Resin (X2)	Cap. @ 6 lbs. K Grains (X2)	Brine Tank Size
F30F2GEM	9X42	F2TT	5.3	1.0	26.6	15"X15"X35"
F40F2GEM	10X44	F2TT	6.5	1.3	33.2	15"X15"X35"
F50F2GEM	10X54	F2TT	9.0	1.7	40.0	15"X15"X35"
F60F2GEM	12X48	F2TT	11.0	2.0	50.0	15"X15"X35"
F75F2GEM	13X54	F2TT	13.0	2.5	60.0	18"X40"
F90F2GEM	14X65	F2TT	17.0	3.0	80.0	18"X40"
F120F2GEM	16X65	F2TT	20.0	4.0	110.0	18"X40"

### Fusion<sup>2</sup> GEMINI CONTROL VALVE SPECIFICATIONS

Inlet/Outlet Fittings	¾" to 1 ½"
Cycles	Up to 9
Regeneration	Upflow or downflow
Max Operating Pressure	125 PSI
Drain Line	¾" or 1" NPT
Service @ 15 PSI Δp	30 USGPM
Power Supply	120VAC
Valve Material:	Noryl or equivalent
Tank Applications (Filter or Softener)	6" - 21"

**Waterite**  
  
*brings pure water to life*

Head Office Winnipeg, MB  
 Warehouse branches in Langley, BC • Barrie, ON  
 St-Laurent, QC • Sarasota FL

MEMBER  
 Water  
 Quality  
 ASSOCIATION