



WATERITE TECHNOLOGIES, INC.
3-75 Meridian Drive
Winnipeg, MB
Canada R2R 2V9
PHONE: (204) 786-1604
FAX: (204) 783-1599
waterite@waterite.com
www.waterite.com

**WATERITE TECHNOLOGIES, INC.
PRODUCT SPECIFICATION SHEET
FIL-SPP-014**

**NX SERIES SPUN POLYPROPYLENE SEDIMENT
FILTER CARTRIDGE**

Certified to ANSI/NSF Standard 42 for material safety and structural integrity only

TYPE: 2 1/2" and 4 1/2" cartridges for 10" and 20" standard and full flow (Big Blue) housings
FEED: Municipal or well water
TEMP. RANGE: 5.0°C to 60.0°C
CAPACITY: determined by raw water turbidity
MICRON RATING: 1, 5 and 20 micron nominal
COLOUR: white
MATERIAL: Virgin melt-blown polypropylene
All materials certified to ANSI/NSF Standard 42 for material safety and structural integrity only, by WQA
PACKAGING MODELS: Plastic shrink wrapped and labeled
PP10-01NX, PP10-05NX, PP10-20NX PP20-01NX, PP20-05NX, PP10B-05NX, PP10B-20NX, PP20B-05NX, PP20B-20NX
PERFORMANCE:

Cartridge Model	Micron Rating	Initial ΔP @ Flow Rate
PP10-01NX	1	0.6 psi @ 5 GPM
PP10-05NX	5	0.2 psi @ 5 GPM
PP10-20NX	20	0.2 psi @ 5 GPM
PP20-01NX	1	0.6 psi @ 10 GPM
PP20-05NX	5	0.6 psi @ 10 GPM
PP10B-05NX	5	≤1 psi @ 10 GPM
PP10B-20NX	20	≤1 psi @ 10 GPM
PP20B-05NX	5	≤1 psi @ 20 GPM
PP20B-20NX	20	≤1 psi @ 20 GPM

CORPORATE MARK:

*Excelpure*TM

CERTIFICATION:



COMPONENT

SPEC FIL-SPP-014

November, 2012