



WATERITE TECHNOLOGIES, INC.
3-75 Meridian Drive
Winnipeg, MB
Canada R2R 2V9
PHONE: (204) 786-1604
FAX: (204) 783-1599
waterite@waterite.com
www.waterite.com

**WATERITE TECHNOLOGIES, INC.
PRODUCT SPECIFICATION SHEET
FIL-PPCC-001**

**SPUN POLYPROPYLENE SEDIMENT &
ACTIVATED 5-MICRON CARBON BLOCK
COMBINATION FILTER CARTRIDGE**

TYPE:	2 ½" cartridges for 10" standard housings
FEED:	Municipal or well water
TEMP. RANGE:	5.0°C to 60.0°C
CAPACITY:	determined by raw water turbidity
MICRON RATING:	5 micron nominal
COLOUR:	white/blue
BODY MATERIAL:	Cartridge end caps: molded polypropylene Internal packing: spun polypropylene
POLYPROPYLENE:	Virgin melt-blown polypropylene
CARBON:	20/50 mesh activated coconut shell GAC
GASKET:	BUNA-N, low durometer
PACKAGING	Plastic shrink wrapped and labeled
MODELS:	<i>Excelpure</i> PPCC10-05



Excelpure™

SPEC FIL-PPCC-001

May, 2005